Phone +49 (0) 5121 2893390

Fax +49 (0) 5121 2893367

E-mail info@heyl.de

Internet www.heyl.de



Safety data sheet according to 1907/2006/EC

Revision: 20.05.2020 Printing date 20.05.2020 Version number 10

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: Testoval Mangan Test 0 20 mg/l B
- · CAS Number:

7790-28-5

· EC number:

232-197-6

- · Registration number 01-2119980983-20
- · **UFI:** XYPS-WT98-CC07-W9K5
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation:

Reagent for analysis

EuPCS: PC-TEC-19 Reagents and laboratory chemical

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Gebrüder Heyl

Analysentechnik GmbH & Co. KG

Orleansstraße 75 b

D-31135 Hildesheim

- · Further information obtainable from: product safety department
- · 1.4 Emergency telephone number:

Giftinformationszentrum Nord

Phone +49 (0) 551 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS03 flame over circle

Ox. Sol. 1 H271 May cause fire or explosion; strong oxidiser.



GHS08 health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



GHS05 corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 1)

· Hazard pictograms









GHS03 GHS05 GHS08 GH

· Signal word Danger

· Hazard-determining components of labelling:

sodium periodate

· Hazard statements

H271 May cause fire or explosion; strong oxidiser. H314 Causes severe skin burns and eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Precautionary statements

P210 Keep away from heat. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

· Labelling of packages where the contents do not exceed 125 ml

Hazard pictograms









GHS03 GHS05 GHS08 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

sodium periodate

· Hazard statements

H271 May cause fire or explosion; strong oxidiser.

H314 Causes severe skin burns and eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- · 3.1 Substances
- · CAS No. Description

7790-28-5 sodium periodate

- · Identification number(s)
- · EC number: 232-197-6
- · SVHC Not applicable.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

Call a doctor immediately.

· After eye contact:

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing:

A person vomiting while laying on their back should be turned onto their side.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In the event of decomposition: danger of explosion!

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose of the material collected according to regulations.

Clean the affected area carefully; suitable cleaners are:

Warm water

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Substance/product is oxidising when dry.

Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility:

Store away from flammable substances.

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in dry conditions.

Store receptacle in a well ventilated area.

- Recommended storage temperature: 15 25 °C
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2

Protection of hands:



Protective gloves

Wear gloves according to EN 374.

(Contd. on page 5)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check protective gloves prior to each use for their proper condition.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.12 mm Value for the permeation: Level = 6 (> 480 min)

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

General Information

Recommended thickness of the material: ≥ 0.12 mm Value for the permeation: Level = 6 (> 480 min)

Eye protection:



Tightly sealed goggles according to EN 166

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

Appearance:	0-1:-1
Form: Colour:	Solid White
· Odour:	Odourless
· Odour threshold:	Not determined.
· pH-value (50 g/l) at 20 °C:	5.2
· Change in condition Melting point/freezing point:	Undetermined

Initial boiling point and boiling range: Undetermined.

Flash point:

Undetermined.

Flammability (solid, gas): Product is not flammable.
 Ignition temperature: Not determined.
 Decomposition temperature: 290 - 300 °C
 Auto-ignition temperature: Not determined.
 Explosive properties: Product does not present an explosion hazard. Explosive when mixed with combustible material.

· Explosion limits:

Lower: Not determined.

(Contd. on page 6)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

	(Contd. of page 5
Upper:	Not determined.
· Vapour pressure:	Not applicable.
Density at 20 °C:	3.87 g/cm³
Relative density	Not determined.
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water at 20 °C:	91 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

To avoid thermal decomposition do not overheat.

Explosive thermal decomposition.

· 10.3 Possibility of hazardous reactions

Reacts with flammable substances.

Reacts with powdered metals.

Reacts with acids.

Reacts with reducing agents.

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

ΕU



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 6)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product. Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1	UN-Number
--------	------------------

· ADR, IMDG, IATA

UN1479

14.2 UN proper shipping name

· ADR

1479 OXIDIZING SOLID, N.O.S. (sodium periodate), ENVIRONMENTALLY HAZARDOUS

• IMDG, IATA OXIDIZING SOLID, N.O.S. (sodium periodate)

· 14.3 Transport hazard class(es)

· ADR





Class 5.1 Oxidising substances.

(Contd. on page 8)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

	(Contd. of page
Label	5.1
· IMDG, IATA	
· Class · Label	5.1 Oxidising substances.5.1
· 14.4 Packing group · ADR, IMDG, IATA	I
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	No Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Segregation Code	Warning: Oxidising substances. 50 F-A,S-Q D SG38 Stow "separated from" SGG2-ammoniu compounds. SG49 Stow "separated from" SGG6-cyanides SG60 Stow "separated from" SGG16-peroxides SG61 Stow "separated from" SGG15-powdere metals
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Void
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	1 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1479 OXIDIZING SOLID, N.O.S. (SODIU PERIODATE), 5.1, I, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category

P8 OXIDISING LIQUIDS AND SOLIDS

E1 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t

(Contd. on page 9)



Printing date 20.05.2020 Version number 10 Revision: 20.05.2020

Trade name: Testoval Mangan Test 0 - 20 mg/l B

(Contd. of page 8)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department.
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Ox. Sol. 1: Oxidizing solids - Category 1

Skin Corr. 1C: Skin corrosion/irritation – Category 1C Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

* Data compared to the previous version altered.

ΕU